



STONIMAGE

How to be A Global Leader in Services?

Many of us are facing after-sales trouble no matter private or governmental control company, time is invaluable and most worrying for us. Once the machine shut down, the production shut down either, and we start to lose money quickly and come to an operation crisis So what we do here?

- ◆ Fast Action in Services
- ◆ Unconditional Parts Supply
- ◆ Strong Professionalism

XINXIANG STONIMAGE TECHNOLOGY CO. LTD
新乡市石像科技有限公司

Tel: +86 373 5853611 +86 173 3736 9213

www.stonimagelift.com

Add: 1522#, Gongyuanguoji, Hongqi district, Xinxiang city, Henan, China

STONIMAGE

was founded at end of 2014, is a global brand and manufacturer of lifting equipment and material handling equipment, we owns the most professional engineering team, R & D center and manufacturing base with rich experience in lifting industry. We are working with full passion in continuous innovation and improving services level.

Currently, STONIMAGE is focusing on Innovation, Manufacturing and Supplying of various lifting equipment, transportation machinery and construction machinery, mainly as below:

- Ladder Lift, Solar Panel Lift, Glass and window lift, Glass trolley
- Cargo truck elevator, Fish elevator, Mountain cargo Lift
- Electric scaffold, Wall building platform
- Electric forklift, Brick stacker, Installation Forklift for Pipe/Panel
- Scissor lift, Retractable stairs, Belt conveyor
- Restaurant Meal elevator



- **Aerial Ladder Lift**
- ✓ For Solar panel
- ✓ For Glass/window/door
- ✓ For Construction material




- **Cargo Truck Loader**
- **Fish Truck Loader**



Electric Cargo Lift

- ✓ Max. Lifting Capacity: 300kg/ 400kg / 500kg
- ✓ Lifting height: 2~15m
- ✓ For lifting cargo



Technical Data

Platform Height (m)	Max. Lifting Capacity (kg)	Platform size (m)	Dimension (m)	Dead weight (kg)	Material
2	300	1.0*0.8	1*0.8*3.4	200	4*6 steel pipe, 2mm thickness
2.5	300	1.0*0.8	1*0.8*3.9	225	4*6 steel pipe, 2mm thickness
3	300	1.0*0.8	1*0.8*4.4	250	4*6 steel pipe, 2mm thickness
3.5	300	1.0*0.8	1*0.8*4.9	275	4*6 steel pipe, 2mm thickness
4	300	1.0*0.8	1*0.8*5.4	300	4*6 steel pipe, 2mm thickness
4.5	300	1.0*0.8	1*0.8*5.9	325	4*6 steel pipe, 2mm thickness
5	300	1.0*0.8	1*0.8*6.4	350	4*6 steel pipe, 2mm thickness
6	300	1.0*0.8	1*0.8*7.4	400	4*6 steel pipe, 2mm thickness
7	300	1.0*0.8	1*0.8*8.4	450	4*6 steel pipe, 2mm thickness
8	300	1.0*0.8	1*0.8*9.4	500	4*6 steel pipe, 2mm thickness
9	300	1.0*0.8	1*0.8*10.4	550	4*6 steel pipe, 2mm thickness
10	300	1.0*0.8	1*0.8*11.5	600	4*6 steel pipe, 2mm thickness
15	500	1.0*0.8	1*0.8*16.5	800	4*6 steel pipe, 2mm thickness

Technical Notes:

- 1) Motor size: PA800/PA1000
- 2) Standard voltage: 220V
- 3) Control: Remote control
- 4) Wire Rope diameter: 6mm
- 5) Safety protection: Upper and lower limiter, include falling protector
- 6) Packing: Wooden case (especially for export)



Application 应用案例

